



# KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7<sup>TH</sup> Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,  
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277  
uday.sawant@kei-ind.com / swapnil.kanekar@kei-ind.com



**PRICE LIST : JUL-2020**

**LP NO. KEI/W&F/LP/20-21/02 DT.15.07.2020**

**INDUSTRIAL MULTI STRAND CABLES**

**HSN CODE : 85.44.60.20**

**KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	640	28	1280	12	7.11
0.75	24/0.20	7	865	28	1730	12	9.61
1.00	32/0.20	11	1075	24	2150	12	11.94
1.50	30/0.25	14	1615	16	3230	8	17.94
2.50	50/0.25	19	2615	12	5230	6	29.06
4.00	56/0.30	26	3865	8	7730	4	42.94
6.00	84/0.30	31	5860	6	11720	3	65.11
10.00	80/0.40	42	10520	1			116.89
16.00	126/0.40	57	16390	1			182.11

**KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	700	28	1400	12	7.78
0.75	24/0.20	7	895	28	1790	12	9.94
1.00	32/0.20	11	1135	24	2270	12	12.61
1.50	30/0.25	14	1710	16	3420	8	19.00
2.50	50/0.25	19	2740	12	5480	6	30.44
4.00	56/0.30	26	4055	8	8110	4	45.06
6.00	84/0.30	31	6100	6	12200	3	67.78
10.00	80/0.40	42	11120	1			123.56
16.00	126/0.40	57	17350	1			192.78

**KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.**

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	935	28	1870	12	10.39
1.00	32/0.20	11	1215	24	2430	12	13.50
1.50	30/0.25	14	1790	16	3580	8	19.89
2.50	50/0.25	19	2855	12	5710	6	31.72
4.00	56/0.30	26	4150	8	8300	4	46.11
6.00	84/0.30	31	6280	6	12560	3	69.78
10.00	80/0.40	42	11420	1			126.89
16.00	126/0.40	57	17750	1			197.22

**Notes:**

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.



# KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7TH Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,

Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277

uday.sawant@kei-ind.com / swapnil.kanekar@kei-ind.com



PRICE LIST : JUL-2020

LP NO. KEI/W&F/LP/20-21/02 DT.15.07.2020

PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES

HSN CODE : 85.44.60.20

**KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH
0.5	16/0.20	4	24	710	755	775	35	276/0.4	110	40400	41760	42360
0.75	24/0.20	7	24	960	1005	995	50	396/0.4	145	57940	59950	60750
1.0	32/0.20	12	20	1195	1260	1260	70	354/0.5	200	81220	83990	85040
1.5	30/0.25	16	16	1795	1880	1900	95	484/0.5	235	106970	111270	112630
2.5	50/0.25	22	12	2905	3025	3045	120	608/0.5	270	136810	141940	144480
4.0	56/0.30	29	8	4295	4440	4505	150	750/0.5	310	171440	177900	180100
6	84/0.30	37	4	6510	6755	6780	185	925/0.5	360	207780	215980	218840
10	80/0.40	51	1	11690	12290	12360	240	1210/0.5	425	274280	284850	289060
16	126/0.40	68	1	18210	19180	19280	300	1527/0.5	490	341840	354760	360260
25	196/0.40	86	1	28920	29910	30330	400	2036/0.5	590	452520	462740	469180

**KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	2100	2790	3460	4690	5430	5940	9200	10630	12130	13840	15980	20450
0.75	24/0.20	2840	3640	4690	6480	7400	8150	12400	14400	16630	18950	22010	28110
1.0	32/0.20	3160	4330	5680	7590	9000	10100	15290	17700	20450	23340	27040	34470
1.5	30/0.25	4330	6050	7800	10560	12400	13890	20660	24300	28160	32150	37350	47810
2.5	50/0.25	7020	9710	12720	16780	19840	22160	32710	38730	45290	51430	60210	76870
4.0	56/0.3	11000	15560	20160	27410	31400	36380	53520	63460	73600	83760	98340	126380

6	84/0.3	15790	22660	29920	39260	
10	80/0.4	26810	38470	50740	66830	
16	126/0.4	41250	59100	78030		
25	196/0.4		96030	126060		
35	276/0.4		133540	174140		
50	396/0.4		191240	249980		
70	354/0.5		263870	347200		
95	484/0.5		0	459390		
120	608/0.5					

Note :

**KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS**

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	6390
2.5	50/0.25	9890
4	56/0.3	14910
6	84/0.3	22290
10	80/0.4	36650
16	126/0.4	57910
25	196/0.4	87480

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
  - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
  - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
  - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
  - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
  - Single Core 10sqmm and above will be supplied in single coil packing.
  - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.

**KEI WIRES & CABLES**